

Parameter	Reportable Range	Resolution	Measurement method
pH (pH units)	6.5 – 8.0	0.001	Potentiometric sensor
pO ₂ (mmHg)	10 – 700	0.1	Amperometric sensor
pCO ₂ (mmHg)	10 – 150	0.1	Potentiometric sensor
Na (mmol/L)	100 – 180	0.1	Potentiometric sensor
K (mmol/L)	2.0 – 9.0	0.01	Potentiometric sensor
Ca (mmol/L)	0.25 – 2.5	0.01	Potentiometric sensor
CI (mmol/L)	65 – 140	0.1	Potentiometric sensor
Glu (mg/dL or mmol/L)	20 - 700/1.1 - 38.9	1/0.1	Amperometric sensor
Lac (mg/dL or mmol/L)	2.7 – 180.2/0.3 -20	0.1/0.01	Amperometric sensor
Hct (%PCV or Fraction)	10 – 75 /0.10 – 0.75	1%/0.01	Conductance sensor

Specification

Throughput	Results in 1 minute after sample aspiration				
Sample volume	140µl				
Quality control	3 or 5 levels QC, External electronic simulator				
Display	7-inch color LCD Display, 800*480				
Interface	4 x USB 2.0 host, 1 x RS232, WLAN				
Input device	Touch screen and barcode scanner				
Power supply	100~240VAC, 50/60Hz				
Battery	4200mAh rechargeable lithium-ion battery, 50 samples continuous testing				
Dimensions (W*H*D)	238*153*310 mm				
Weight	3.65 KG				
Operation Environment	10 °C-31 °C; %RH: 25%-80%; 70 -106.6 KPa				

About Edan

Edan is a healthcare company dedicated to improving the human condition around the world by delivering value-driven, innovative and high-quality medical products and services. For over 20 years, Edan has been pioneering a comprehensive line of medical solutions that address a broad range of healthcare practices including:

- Diagnostic ECG
- Ultrasound Imaging
- In-Vitro Diagnostics

- Patient Monitoring
- Point-of-Care Testing
- Veterinary

• OB/GYN

Healthcare professionals around the world depend on Edan's breakthrough medical technologies and outstanding customer support.



Edan Instruments, Inc. | 3/F-B, Nanshan Medical Equipments Park, 1019# Nanhai Rd., Shenzhen | 518067 P.R. China +86.755.26898326 | www.edan.com.cn | info@edan.com.cn



i15
Blood Gas and Chemistry Analyzer









Portable, lightweight

- Capable to run 50 samples with fully-charged battery
- · Diagnose at the point of care, patient side, out in the field or exam room

Easy, Quick and Convenient

- Zero maintenance
- Minimize hands on time and training requirement
- Auto-sampling
- Report is ready within one minute after sample aspiration

Accurate and Reliable

- · Innovative microchip liquid control technology and micro-sensor multifunction membrane technology
- High sensitivity and accuracyCalibrator, Control and Electronic simulator to TRIPLE guarantee the RESULTS!

- Flexible Data Management
 Acquire patients' information via barcode/QR code
- Up to 10,000 patient data storage
- 4 USB ports and LAN/WiFi for data management
- Optional data management software

Multi-parameter cartridge

- · Multi popular time-sensitive parameters come in one cartridge, including ABG, electrolytes and metabolites
- Single-use cartridge avoids contamination
- Room temperature storage with long shelf-life





i15 Quality Control System

Triple Guarantee the Result



Variety of test Cartridges

i15 trailer

	рН	pCO ₂	pO ₂	Na	K	CI	Ca	Hct	Glu	Lac
BG3										
BG8			_	_	_		_			
BG4										
BG9										
BG10										
BC4										

Calculated values: cH+, HCO3-act, HCO3-std, BE(ecf), BE(B), BB(B), ctCO2, sO2(est), Ca++(7.4), AnGap, tHb(est), pO2(A-a), pO2(a/A), RI, pO2/FIO2, cH+(T), pH(T), pCO₂(T), pO₂(T), pO₂(A-a)(T), pO₂(a/A)(T), RI(T), pO₂(T)/FIO₂